

# A-O MODULATOR / FREQUENCY SHIFTER

## (MODEL AOM-AF1 SERIES)

- Intensity Modulation
- Optical Frequency Shifting
- Laser Beam deflection
- High Optical Power Capability
- High Reliability
- Excellent Temperature Stability



SPECIFICATION	
Optical Wavelength Range	440 to 700 nm
Acousto-optic Material	Dense Flint Glass
Acoustic Velocity	3630 m/sec
Active Aperture Height <sup>1</sup>	2 mm
Modulation Bandwidth (-3db)	2.7 MHz (1.0 mm beam diameter) 1.8 MHz (1.5 mm beam diameter)
Optical Rise Time	177 nsec (1.0 mm beam diameter) 265 nsec (1.5 mm beam diameter)
Static Optical Insertion Loss	2 Percent (633nm)
Optical Polarization	Any
RF Input Impedance	50 Ohms (VSWR < 1.25:1 at CF)
RF Connector	BNC
Size (less connector)	0.88 H x 2.94 D x 2.46 W inches 22.4 H x 74.7 D x 62.5 W mm

Model	AOM-602AF1	AOM-802AF1	AOM-1002AF1
Center Frequency <sup>2</sup>	60 MHz	80 MHz	100 MHz
Optical Frequency Shift Range	±(50 to 70)MHz	±(65 to 95)MHz	±(85 to 115)MHz
Diffraction Efficiency	90 Percent	90 Percent	85 Percent
Drive Power <sup>3</sup>	2 Watts (633 nm) 9.6	2 Watts (633 nm)	2 Watts (633 nm)
Beam Separation	mrad (633 nm)	12.8 mrad (633 nm)	17.3 mrad (633 nm)

<sup>1</sup> Other active aperture heights available.

<sup>2</sup> Other center frequencies available.

<sup>3</sup> A complete line of analog, digital, dual frequency, OEM, and laboratory drive electronics are available.

